



Italian excellence since 1906



PUMPS AND ACCESSORIES CATALOG

ABOUT US

Pedrollo Group USA serves as the North American office for Pedrollo Group Srl, catering to the United States and Canada. Established in 1974 in San Bonifacio (Verona), Pedrollo S.p.A. remains a prominent industrial entity in Northeastern Italy and it holds a global reputation as a benchmark in the electric water pumps industry.

Pedrollo Group Srl focuses on WATER, ENERGY, and TECHNOLOGY sectors, upholding its tradition of innovation and technology, reflecting the excellence of its Italian heritage. The company boasts a diverse collection of renowned brands, such as Pedrollo®, Panelli®, City Pumps®, LINZ Electric®, Superior Pump®, Saci Pumps®, PM Technology®, and Gread Electronics®, catering to various market applications, including residential, commercial, industrial, agricultural, irrigation, and swimming pools. Our Panelli® global brand has boasted Italian and global excellence in water pump design, since origination in 1906.

Our extensive Panelli® product line is specifically engineered to address the needs of residential and light commercial environments, offering solutions for basement dewatering, general clean water and wastewater management, and offers preassembled systems aimed at optimizing operational efficiencies and yielding favorable economic outcomes for our customers.

Quality, trust, service, professionalism, and internationalization, as well as a commitment to social responsibility, are the cornerstones of Pedrollo Group Srl's long-standing global reputation and is echoed by every brand. For more information on our social responsibility initiatives, please visit www.pedrollo4people.com.

For 7 days a week customer service, domestically based in St. Paul, MN please reach out to customer.service@pedrollogroupusa.com or call **800.495.9278**.



INDEX

| | |
|--|--------------|
| About/ Support..... | 1 |
| Index..... | 2 |
| Utility Pumps..... | 3-6 |
| - Submersible Pumps..... | 3-5 |
| - Transfer Pumps | 6 |
| Sump Pumps..... | 7-11 |
| - Submersibles | 7-8 |
| - Pedestals | 9 |
| - Battery Backup Systems..... | 9 |
| - Combination Primary & Battery Back-Up Systems..... | 10 |
| - Remote Drain & Crawl Space Systems | 11 |
| Effluent Pumps | 12 |
| Sewage Pumps..... | 13-14 |
| - Sewage Pumps | 13 |
| - Preassembled Sewage Systems | 14 |
| Specialty..... | 15-17 |
| - Tankless Water Heater Descaler Kit | 15 |
| - Condensate Pumps..... | 15 |
| - Portable Lawn Sprinkler..... | 16 |
| - Oil-Defender™ Elevator Sump Pump System with Alarm | 16 |
| - Bronze Transfer Pumps..... | 17 |
| Well Pumps..... | 18-19 |
| - Shallow Well, Jet Pump and Tank Systems | 18 |
| - Convertible Well, Jet Pump and Tank Systems | 18 |
| Accessories..... | 20-24 |
| Contact Us/Sales | 25-26 |

UTILITY PUMPS


Our Panelli® range of multi-purpose utility pumps offers a variety of submersible and non-submersible designs, providing a versatile solution for efficiently transferring water from one location to another. These pumps are designed to expedite installation and maintenance tasks, whether it involves draining a clogged bathtub, charging polyglycol lines, dewatering a flooded basement, emptying a water heater. Additionally, a 12 Volt option is available to cater to diverse requirements.

Our submersible utility pump line is engineered for durability, featuring a solid copper wound, thermally protected PSC motor. Equipped with double o-ring seals and heavy-duty mechanical shaft seals, these pumps deliver enduring, quiet, and leak-free performance. With flow rates reaching up to 98 gallons per minute, our range encompasses 1 HP pumps for substantial tasks all the way down to 1/5 HP pumps, for smaller applications.

Furthermore, we offer multi-use 115V/60Hz pumps with 10 ft. and 25 ft. power cord lengths to meet professional demands. For remote locations, our 12 volt DC submersible and/or transfer pumps ensure reliable water transfer.



- A** Carrying Handle
- B** Permanent Split Capacitor Motor
- C** Solid Copper Motor Windings
- D** Double Seals on Motor Plate
- E** Removable Intake Screen
- F** Heavy Duty Shaft Seal



12 Volt DC

Thermoplastic



- Multiple applications: marine, home, outdoors, camping / RV, hunting, farm and more
- Works with most 12 volt batteries (not included)
- Tough thermoplastic construction
- 1-1/4" NPT discharge
- 3/4" Garden hose adapter included
- 20' Battery cables
- On / off switch


23 Gallons Per Minute | **3** Year Warranty

| Model | Volts | On/Off | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|----------|-------|--------|---------------|----------------|----------------|------|--------|----------|
| PAN91012 | 12 | Yes | Thermoplastic | 1-1/4" | Top | 20' | 1/8" | 3 Years |

Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 23 | 1380 |
| 5' | 22 | 1320 |
| 10' | 18 | 1080 |
| 15' | 13 | 780 |
| 20' | 8 | 480 |

Based on 1-1/4" PVC discharge pipe



1/5 - 1/4 - 1/3 HP

Thermoplastic



26 | 3 Year Warranty
Gallons Per Minute

30 | 3 Year Warranty
Gallons Per Minute


40 | 3 Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|----------|-----|------|---------------|----------------|----------------|------|--------|----------|
| PAN91025 | 1/5 | 3.6 | Thermoplastic | 1-1/4" | Top | 10' | 1/8" | 3 Years |
| PAN91026 | 1/5 | 3.6 | Thermoplastic | 1-1/4" | Top | 25' | 1/8" | 3 Years |
| PAN91250 | 1/4 | 3.8 | Thermoplastic | 1-1/4" | Top | 10' | 1/8" | 3 Years |
| PAN91255 | 1/4 | 3.8 | Thermoplastic | 1-1/4" | Top | 25' | 1/8" | 3 Years |
| PAN91330 | 1/3 | 4.1 | Thermoplastic | 1-1/4" | Top | 10' | 1/8" | 3 Years |
| PAN91355 | 1/3 | 4.1 | Thermoplastic | 1-1/4" | Top | 25' | 1/8" | 3 Years |

- Pump will lift water up to 25' of vertical height
- Tough thermoplastic construction
- 1-1/4" NPT discharge
- 3/4" garden hose adapter included
- Can be used as a sump pump by adding an optional float switch (See accessories section, pg 20)
- Thermoplastic impeller

| Performance | Head | PAN91025 PAN91026 | | PAN91250 PAN91255 | | PAN91330 PAN91355 | |
|-------------|------|----------------------|------|----------------------|------|----------------------|------|
| | | GPM | GPH | GPM | GPH | GPM | GPH |
| | 0' | 26 | 1560 | 30 | 1800 | 40 | 2400 |
| | 5' | 21 | 1260 | 22 | 1320 | 34 | 2040 |
| | 10' | 14 | 840 | 20 | 1200 | 28 | 1680 |
| | 15' | 10 | 600 | 16 | 960 | 22 | 1320 |
| | 20' | 7 | 420 | 9 | 540 | 12 | 720 |
| | 25' | 1 | 60 | 2 | 120 | 2 | 120 |

Based on 1-1/4" PVC discharge pipe



1/2 HP

Thermoplastic




55 Gallons Per Minute | **3** Year Warranty

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|----------|-----|------|---------------|----------------|----------------|------|--------|----------|
| PAN91570 | 1/2 | 4.9 | Thermoplastic | 1-1/2" | Side | 10' | 3/8" | 3 Years |
| PAN91575 | 1/2 | 4.9 | Thermoplastic | 1-1/2" | Side | 25' | 3/8" | 3 Years |

- Pump will lift water up to 25' of vertical height
- Tough thermoplastic construction with stainless steel impeller
- 1-1/2" discharge for high capacity pumping
- 3/4" garden hose adapter included
- Can be used as a sump pump by adding an optional float switch (See accessories section, pg 20)

| Performance | Head | GPM | GPH |
|-------------|------|-----|------|
| | 0' | 55 | 3300 |
| | 5' | 48 | 2880 |
| | 10' | 42 | 2520 |
| | 15' | 34 | 2040 |
| | 20' | 25 | 1500 |
| | 25' | 16 | 960 |

Based on 1-1/2" PVC discharge pipe



SUBMERSIBLE UTILITY PUMPS

1/3 & 1/2 HP

Stainless Steel



- Pump will lift water up to 30' of vertical height
- Stainless steel housing and impeller
- 1-1/4" NPT discharge
- Can be used as a sump pump by adding an optional float switch (See accessories section, pg 20)
- Pumps down to 1/8" from surface with removable thermoplastic shroud installed




55 | 3 Year Warranty
Gallons Per Minute

74 | 3 Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|----------|-----|------|-----------------|----------------|----------------|------|--------|----------|
| PAN91392 | 1/3 | 6 | Stainless Steel | 1-1/4" | Top | 25' | 3/8" | 3 Years |
| PAN91592 | 1/2 | 8.5 | Stainless Steel | 1-1/4" | Top | 25' | 3/8" | 3 Years |

| Performance | PAN91392 | | PAN91592 | |
|-------------|----------|-----|----------|-----|
| | Head | GPM | GPH | GPM |
| | 0' | 55 | 3300 | 74 |
| | 5' | 49 | 2940 | 64 |
| | 10' | 40 | 2400 | 55 |
| | 15' | 30 | 1800 | 45 |
| | 20' | 22 | 1320 | 39 |
| | 25' | 11 | 660 | 29 |
| | 30' | - | - | 17 |

Based on 1-1/4" PVC discharge pipe



1 HP

Stainless Steel



- Pump will lift water up to 30' of vertical height
- 1-1/2" NPT discharge
- 1-1/2" NPT x 1-1/2" barb 90° elbow adapter included
- Stainless steel impeller & intake screen
- Can be used as a sump pump by adding an optional float switch (See accessories section, pg 20)
- Integrated heavy-duty handle for easy transport




98 Gallons Per Minute | 3 Year Warranty

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|----------|----|------|-----------------|----------------|----------------|------|--------|----------|
| PAN91197 | 1 | 11.4 | Stainless Steel | 1-1/2" | Side | 25' | 1/8" | 3 Years |

| Head | GPM | GPH |
|------|-----|------|
| 0' | 98 | 5898 |
| 5' | 83 | 4980 |
| 10' | 64 | 3840 |
| 15' | 49 | 2940 |
| 20' | 31 | 1860 |
| 25' | 17 | 1020 |
| 30' | 5 | 300 |

Based on 1-1/2" PVC discharge pipe



12 Volt Transfer Pump

Aluminum



- Includes 6' suction hose, suction attachment, extra impeller and gasket kit
- 7' Battery cables
- On/off switch included
- Convenient carrying handle
- 3/4" Garden hose connections
- Self priming up to 7' depth
- Works great for draining boats, kids pools, water heaters, water beds, washing machines and more


5.5 Gallons Per Minute | **1 Year Warranty**

| Model | Volts | Construction | Suction/Discharge Size | Cord | Cooling Type | Warranty |
|----------|-------|--------------|------------------------|------|--------------|----------|
| PAN90045 | 12 | Aluminum | 3/4" GHT | 7' | Fan | 1 Year |

Performance


| Head | GPM | GPH |
|------|-----|-----|
| 0' | 5.5 | 330 |
| 10' | 4.5 | 270 |
| 20' | 3.3 | 198 |
| 30' | 1.9 | 114 |
| 35' | 1 | 60 |

Based on 3/4" discharge



115 Volt Transfer Pump

Aluminum



- Includes 6' suction hose, suction attachment, extra impeller and gasket kit
- 10' Power cord
- Convenient carrying handle
- 3/4" garden hose connections
- Self priming up to 7' depth
- Works great for draining water heaters, water beds, washing machines and more


5.5 Gallons Per Minute | **1 Year Warranty**

| Model | Volts | Amps | Construction | Suction/Discharge Size | Cord | Cooling Type | Warranty |
|----------|-------|------|--------------|------------------------|------|--------------|----------|
| PAN90040 | 115 | 2.3 | Aluminum | 3/4" GHT | 10' | Fan | 1 Year |

Performance

| Head | GPM | GPH |
|------|-----|-----|
| 0' | 5.5 | 330 |
| 10' | 4.5 | 270 |
| 20' | 3.3 | 198 |
| 30' | 1.9 | 114 |
| 35' | 1 | 60 |

Based on 3/4" discharge



1/2 HP Transfer Pump

Cast Iron



- Rugged cast iron construction
- 3/4" NPT suction & discharge
- Heavy duty power cord
- On/off switch
- Includes: brass garden hose adapters, suction strainer and an additional set of motor brushes
- Multiple Uses: Drain water heaters, fill radiant heating systems, and general water transfer
- Heavy duty steel handle, easy prime plug


26 Gallons Per Minute | **1 Year Warranty**

| Model | HP | Amps | Construction | Suction Size | Discharge Size | Cord | Motor Brushes | Warranty |
|----------|-----|------|--------------|--------------|----------------|------|---------------|----------|
| PAN90050 | 1/2 | 8.4 | Cast Iron | 3/4" NPT/GHT | 3/4" NPT/GHT | 10' | Replaceable | 1 Year |
| PAN90060 | 1/2 | 8.4 | Cast Iron | 3/4" NPT/GHT | 3/4" NPT/GHT | 25' | Replaceable | 1 Year |

Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 25 | 1500 |
| 20' | 19 | 1140 |
| 40' | 13 | 780 |
| 60' | 7 | 420 |
| 80' | 3 | 180 |
| 100' | .8 | 50 |

Based on 3/4" discharge



TRANSFER UTILITY PUMPS

SUMP PUMPS

Panelli® offers a comprehensive range of primary pumps for sump applications designed for reliable, continuous use. These pumps feature a solid copper wound, thermally protected PSC motor, double O-ring seals, and heavy-duty mechanical shaft seals for long-lasting, quiet, and leak-free performance. They are constructed using high-quality materials such as corrosion-resistant stainless steel, epoxy-coated cast iron, and fiberglass-reinforced thermoplastic. Our primary pumps are available in 1/4 HP to 1 HP models capable of moving up to 100 GPM of water.

In addition to our primary pumps, we provide reliable standby 12V DC powered systems made of fiberglass-reinforced thermoplastic for protection during power outages. With models designed to perform up to 45 GPM water removal, these are your first line of defense in a power outage. Each are available with a proven tether float or vertical float switch option.

Panelli® makes it easier for you, and offers completely preassembled and preplumbed primary and backup sump pump systems, as well as an assortment of heavy duty basins as needed, to simply save you time, streamline your installation processes, reaping the rewards of optimized efficiencies.



- A** Carrying Handle
- B** Vertical or Tether Operation
- C** Permanent Split Capacitor Motor
- D** Solid Copper Motor Windings
- E** Double Seals on Motor Plate
- F** Removable Intake Screen
- G** Heavy Duty Shaft Seal

1/4 & 1/3 HP

Thermoplastic



- Pump will lift water up to 25' of vertical height
- Thermoplastic construction
- 1-1/4" or 1-1/2" discharge for high capacity pumping
- SJE Rhombus® float switch with piggyback power plug




30 | 3 Year Warranty
Gallons Per Minute

40 | 3 Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch | Cord | Solids | Warranty |
|----------|-----|------|---------------|-----------------|----------------|----------|------|--------|----------|
| PAN92260 | 1/4 | 3.8 | Thermoplastic | 1-1/4" - 1-1/2" | Top | Vertical | 10' | 1/8" | 3 Years |
| PAN92342 | 1/3 | 4.1 | Thermoplastic | 1-1/4" - 1-1/2" | Top | Vertical | 10' | 1/8" | 3 Years |

| | PAN92260 | | PAN92342 | |
|-----|----------|-----|----------|-----|
| | Head | GPM | GPH | GPM |
| 0' | | 30 | 1800 | 40 |
| 5' | | 22 | 1320 | 34 |
| 10' | | 20 | 1200 | 28 |
| 15' | | 16 | 960 | 22 |
| 20' | | 9 | 540 | 12 |
| 25' | | 2 | 120 | 2 |

Based on 1-1/2" PVC discharge pipe



1/3 HP

Thermoplastic



- Pump will lift water up to 25' of vertical height
- Thermoplastic construction
- 1-1/2" discharge for high capacity pumping
- SJE Rhombus® float switch with piggyback power plug


48 Gallons Per Minute | **3** Year Warranty

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch | Cord | Solids | Warranty |
|----------|-----|------|---------------|----------------|----------------|----------|------|--------|----------|
| PAN92370 | 1/3 | 4.1 | Thermoplastic | 1-1/2" | Side | Tether | 10' | 3/8" | 3 Years |
| PAN92372 | 1/3 | 4.1 | Thermoplastic | 1-1/2" | Side | Vertical | 10' | 3/8" | 3 Years |

Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 48 | 2880 |
| 5' | 44 | 2640 |
| 10' | 40 | 2400 |
| 15' | 36 | 2160 |
| 20' | 23 | 1380 |
| 25' | 16 | 960 |

Based on 1-1/2" PVC discharge pipe



1/3 & 1/2 HP

Cast Iron



- Pump will lift water up to 25' of vertical height
- Rugged cast iron construction
- Stainless steel impeller
- 1-1/2" discharge for high capacity pumping
- SJE Rhombus® float switch with piggyback power plug

46 | **5** Year Warranty
Gallons Per Minute


55 | **5** Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|----------------|----------|------|--------|----------|
| PAN92341 | 1/3 | 4.1 | Cast Iron | 1-1/2" | Side | Vertical | 10' | 3/8" | 5 Years |
| PAN92331 | 1/3 | 4.1 | Cast Iron | 1-1/2" | Side | Tether | 10' | 3/8" | 5 Years |
| PAN92541 | 1/2 | 4.9 | Cast Iron | 1-1/2" | Side | Vertical | 10' | 3/8" | 5 Years |
| PAN92531 | 1/2 | 4.9 | Cast Iron | 1-1/2" | Side | Tether | 10' | 3/8" | 5 Years |

Performance

| Head | GPM | GPH | GPM | GPH |
|------|-----|------|-----|------|
| 0' | 46 | 2760 | 55 | 3300 |
| 5' | 36 | 2160 | 49 | 2940 |
| 10' | 30 | 1800 | 40 | 2400 |
| 15' | 25 | 1500 | 29 | 1740 |
| 20' | 12 | 720 | 18 | 1080 |
| 25' | 1 | 60 | 8 | 480 |

Based on 1-1/2" PVC discharge pipe



1/3 & 1/2 HP

Cast Iron



- Pump will lift water up to 25' of vertical height
- Rugged cast iron construction
- Thermoplastic impeller
- 1-1/2" discharge for high capacity pumping
- SJE Rhombus® vertical float switch with piggyback power plug

60 | **5** Year Warranty
Gallons Per Minute


70 | **5** Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|----------------|----------|------|--------|----------|
| PAN92352 | 1/3 | 5.9 | Cast Iron | 1-1/2" | Side | Vertical | 10' | 1/2" | 5 Years |
| PAN92511 | 1/2 | 7.6 | Cast Iron | 1-1/2" | Side | Vertical | 10' | 1/2" | 5 Years |

Performance

| Head | GPM | GPH | GPM | GPH |
|------|-----|------|-----|------|
| 0' | 60 | 3600 | 70 | 4200 |
| 5' | 56 | 3360 | 66 | 3960 |
| 10' | 50 | 3000 | 58 | 3480 |
| 15' | 35 | 2100 | 48 | 2880 |
| 20' | 15 | 900 | 25 | 1500 |
| 25' | 6 | 360 | 10 | 600 |

Based on 1-1/2" PVC discharge pipe



SUBMERSIBLE SUMP PUMPS

1/3 & 1/2 Pedestal

Stainless Steel / Cast Iron



- Cast iron base
- Fully adjustable automatic switch
- Non-corrosive stainless steel drive shaft, impeller and float ball
- Metal switch arm for strength and durability
- 1-1/2" discharge for high capacity pumping
- For use in sump basins 12" or larger




50 | 5 Year Warranty
Gallons Per Minute

60 | 5 Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Column Material | Cord | Warranty |
|----------|-----|------|--------------|----------------|----------------|-----------------|------|----------|
| PAN92301 | 1/3 | 2.76 | Cast Iron | 1-1/2" | Side | Stainless Steel | 10' | 5 Years |
| PAN92551 | 1/2 | 3.06 | Cast Iron | 1-1/2" | Side | Stainless Steel | 10' | 5 Years |

| | PAN92301 | | PAN92551 | |
|------|----------|------|----------|------|
| Head | GPM | GPH | GPM | GPH |
| 0' | 50 | 3000 | 60 | 3600 |
| 5' | 45 | 2700 | 55 | 3300 |
| 10' | 38 | 2280 | 45 | 2700 |
| 15' | 35 | 2100 | 30 | 1800 |
| 20' | 15 | 900 | 12 | 720 |
| 25' | - | - | 5 | 300 |

Based on 1-1/2" PVC discharge pipe



12 Volt Battery Backup Sump System

Thermoplastic



- 12V DC pump with tether or vertical float switch and mounting hardware
- Full flow check valve
- Alarm/control unit with fuse and mute feature
- Thermoplastic battery box
- 2 amp DC charger with power cord
- Battery sold separately




23 Gallons Per Minute | **3** Year Warranty

| Model | Volts | Construction | Discharge Size | Switch Type | Cord | Solids | Warranty |
|-----------|-------|---------------|------------------|-------------|------|--------|----------|
| PAN92900 | 12 | Thermoplastic | 1-1/4" or 1-1/2" | Tether | 10' | 1/8" | 3 Years |
| PAN929210 | 12 | Thermoplastic | 1-1/4" or 1-1/2" | Vertical | 10' | 1/8" | 3 Years |

| Head | GPM | GPH |
|------|-----|------|
| 0' | 23 | 1380 |
| 5' | 22 | 1320 |
| 10' | 18 | 1080 |
| 15' | 13 | 780 |
| 20' | 8 | 480 |

Based on 1-1/2" PVC discharge pipe



12 Volt Battery Backup Sump System

Thermoplastic



- 12V DC pump with vertical float switch and mounting hardware
- Full flow check valve
- 5 amp DC charger with power cord
- Alarm/control unit with fuse and mute feature
- Thermoplastic battery box
- Automatically tests system every 14 days
- Battery sold separately




45 Gallons Per Minute | **3** Year Warranty

| Model | Volts | Construction | Discharge Size | Switch Type | Cord | Solids | Warranty |
|----------|-------|---------------|----------------|-------------|------|--------|----------|
| PAN92950 | 12 | Thermoplastic | 1-1/2" | Vertical | 10' | 3/8" | 3 Years |

| Head | GPM | GPH |
|------|-----|------|
| 0' | 45 | 2700 |
| 5' | 42 | 2520 |
| 10' | 36 | 2160 |
| 15' | 25 | 1500 |
| 20' | 12 | 720 |

Based on 1-1/2" PVC discharge pipe





Kits Include:

- 12V DC pump with vertical float switch and mounting hardware
- Pump (92372, 92341, 92352, 92511)
- Alarm/control unit with fuse and mute feature

- Thermoplastic battery box
- 2 amp DC charger with power cord
- Preassembled kit is ready to install
- *Battery sold separately*

Model: 12V Backup Pump

| Pump | HP | Power | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|--------|----|-------|---------------|------------------|----------------|------|--------|----------|
| Backup | - | 12V | Thermoplastic | 1-1/4" or 1-1/2" | Top | 10' | 1/8" | 3 Years |

23 Gallons Per Minute | **3** Year Warranty

Backup Pump Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 23 | 1380 |
| 5' | 22 | 1320 |
| 10' | 18 | 1080 |
| 15' | 13 | 780 |
| 20' | 8 | 480 |

Model PAN92972

| Pump | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|---------|-----|------|---------------|----------------|----------------|------|--------|----------|
| Primary | 1/3 | 4.1 | Thermoplastic | 1-1/2" | Side | 10' | 3/8" | 3 Years |

48 Gallons Per Minute | **3** Year Warranty

Primary Pump Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 48 | 2880 |
| 5' | 44 | 2640 |
| 10' | 40 | 2400 |
| 15' | 36 | 2160 |
| 20' | 23 | 1380 |
| 25' | 16 | 960 |

Model PAN92941

| Pump | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|---------|-----|------|--------------|----------------|----------------|------|--------|----------|
| Primary | 1/3 | 4.1 | Cast Iron | 1-1/2" | Side | 10' | 3/8" | 3 Years |

46 Gallons Per Minute | **3** Year Warranty

Primary Pump Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 46 | 2760 |
| 5' | 36 | 2160 |
| 10' | 30 | 1800 |
| 15' | 25 | 1500 |
| 20' | 12 | 720 |
| 25' | 1 | 60 |

Model PAN92952

| Pump | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|---------|-----|------|--------------|----------------|----------------|------|--------|----------|
| Primary | 1/3 | 7.6 | Cast Iron | 1-1/2" | Side | 10' | 1/2" | 3 Years |

60 Gallons Per Minute | **3** Year Warranty

Primary Pump Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 60 | 3600 |
| 5' | 56 | 3360 |
| 10' | 50 | 3000 |
| 15' | 35 | 2100 |
| 20' | 15 | 900 |
| 25' | 6 | 360 |

Model PAN92911


| Pump | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|---------|-----|------|--------------|----------------|----------------|------|--------|----------|
| Primary | 1/2 | 7.6 | Cast Iron | 1-1/2" | Side | 10' | 1/2" | 2 Years |

70 Gallons Per Minute | **3** Year Warranty

Primary Pump Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 70 | 4200 |
| 5' | 66 | 3960 |
| 10' | 58 | 3480 |
| 15' | 48 | 2880 |
| 20' | 25 | 1500 |
| 25' | 10 | 600 |

Performances based on 1-1/2" PVC discharge pipe



- — 12V Backup
- — PAN92972
- — PAN92941
- — PAN92952
- — PAN92911

1/3 HP Remote Drain Pump System

Thermoplastic / Cast Iron



- Drain laundry tubs, washing machines, wet bars, etc.
- Submersible cast iron or thermoplastic sump pumps
- **Basin Features:**
 - Corrosion resistant structural foam
 - Molded reusable PVC Seal
 - 6 gallon capacity
 - 1-1/2" inlet, discharge & vent
- **Check Valve Features:**
 - Full flow design and ABS Construction

48 | 3 Year Warranty
Gallons Per Minute


46 | 3 Year Warranty
Gallons Per Minute

| Kit Model | Pump Model | HP | Amps | Construction | Discharge | Discharge Type | Cord | Solids | Warranty |
|-----------|------------|-----|------|---------------|-----------|----------------|------|--------|----------|
| PAN92072 | PAN92372 | 1/3 | 4.1 | Thermoplastic | 1-1/2" | Side | 10' | 3/8" | 3 Years |
| PAN92017 | PAN92341 | 1/3 | 4.1 | Cast Iron | 1-1/2" | Side | 10' | 3/8" | 3 Years |

Performance

| | PAN92072 | | PAN92017 | |
|------|----------|------|----------|------|
| Head | GPM | GPH | GPM | GPH |
| 0' | 48 | 2880 | 46 | 2760 |
| 5' | 44 | 2640 | 36 | 2160 |
| 10' | 40 | 2400 | 30 | 1800 |
| 15' | 36 | 2160 | 25 | 1500 |
| 20' | 23 | 1380 | 12 | 720 |
| 25' | 16 | 960 | 1 | 60 |

Based on 1-1/2" PVC discharge pipe



1/2 HP Remote Drain Pump System

Thermoplastic / Cast Iron



- Drain laundry tubs, washing machines, wet bars, etc.
- Submersible cast iron or thermoplastic sump pumps
- **Basin Features:**
 - Corrosion resistant structural foam construction
 - Molded reusable PVC Seal
 - 6 gallon capacity
 - 1-1/2" inlet, discharge & vent
- **Check Valve Features:**
 - Full flow design and ABS Construction

55 | 3 Year Warranty
Gallons Per Minute


55 | 3 Year Warranty
Gallons Per Minute

| Kit Model | Pump Model | HP | Amps | Construction | Discharge | Discharge Type | Cord | Solids | Warranty |
|-----------|------------|-----|------|---------------|-----------|----------------|------|--------|----------|
| PAN92034 | PAN92572 | 1/2 | 4.9 | Thermoplastic | 1-1/2" | Side | 10' | 3/8" | 3 Years |
| PAN92051 | PAN92541 | 1/2 | 4.9 | Cast Iron | 1-1/2" | Side | 10' | 3/8" | 3 Years |

Performance

| | PAN92034 | | PAN92051 | |
|------|----------|------|----------|------|
| Head | GPM | GPH | GPM | GPH |
| 0' | 55 | 3300 | 55 | 3300 |
| 5' | 48 | 2880 | 49 | 2940 |
| 10' | 42 | 2520 | 40 | 2400 |
| 15' | 34 | 2040 | 29 | 1740 |
| 20' | 25 | 1500 | 18 | 1080 |
| 25' | 16 | 960 | 8 | 480 |

Based on 1-1/2" PVC discharge pipe



1/3 HP Crawl Space Sump Pump System

Cast Iron



- Cast iron submersible sump pump
- Rugged cast iron construction
- **Basin Features**
 - Perforated sump basin with 18" Slotted cover
 - 15 gallon capacity
- **Hose Kit Features**
 - 1-1/4" x 24' Poly drain tubing
 - 1-1/4" and 1-1/2" hose adapters
 - Rust resistant hose clamps


46 Gallons Per Minute | 3 Year Warranty

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|----------------|----------|------|--------|----------|
| PAN92071 | 1/3 | 4.1 | Cast Iron | 1-1/2" | Side | Vertical | 10' | 3/8" | 3 Years |

Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 46 | 2760 |
| 5' | 36 | 2160 |
| 10' | 30 | 1800 |
| 15' | 25 | 1500 |
| 20' | 12 | 720 |
| 25' | 1 | 60 |

Based on 1-1/2" PVC discharge pipe



EFFLUENT PUMPS

The Panelli® effluent pump portfolio is specifically tailored to meet the rigorous demands of high debris and new construction pits. Our sump/effluent line is engineered with a robust vortex impeller capable of efficiently handling solids up to 1/2 inch. These 1/2 HP up to 1 HP pumps exhibit a performance capacity of up to 100 GPM at 0 feet and can achieve a maximum lift of 50 feet.

Our high head pro-series effluent pumps are meticulously manufactured from heavy-duty epoxy-coated cast iron and/or corrosion-resistant stainless steel, ensuring exceptional resilience in challenging applications. Designed for enduring performance, these pumps feature a solid copper-wound, thermally protected PSC motor, double O-ring seals, and heavy-duty mechanical shaft seals, guaranteeing prolonged, noiseless, and leak-free operation.



- A** Carrying Handle
- B** Vertical or Tether Operation
- C** Permanent Split Capacitor Motor
- D** Solid Copper Motor Windings
- E** Double Seals on Motor Plate
- F** Removable Intake Screen
- G** Heavy Duty Shaft Seal



1/2 HP



- Pump will lift water up to 25' of vertical height
- Rugged stainless steel and cast iron construction
- Large 2" discharge for high capacity pumping
- 1-1/2" NPT adapter included
- Clog resistant stainless steel vortex impeller
- SJE Rhombus® float switch with piggyback power plug




75 Gallons Per Minute | **5 Year Warranty**

| Model | HP | Amps | Construction | Discharge Size | Switch Type | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|-------------|------|--------|----------|
| PAN92581 | 1/2 | 7.5 | SS/Cast Iron | 2" / 1-1/2" | Tether | 10' | 1/2" | 5 Years |
| PAN92571 | 1/2 | 7.5 | SS/Cast Iron | 2" / 1-1/2" | Vertical | 10' | 1/2" | 5 Years |

Stainless Steel / Cast Iron

| Head | GPM | GPH |
|------|-----|------|
| 0' | 75 | 4500 |
| 5' | 70 | 4200 |
| 10' | 64 | 3840 |
| 15' | 57 | 3420 |
| 20' | 49 | 2940 |
| 25' | 40 | 2400 |

Based on 2" PVC discharge pipe



3/4 & 1 HP



- Rugged stainless steel and cast iron construction
- Large 2" discharge for high capacity pumping
- 1-1/2" NPT adapter included
- Clog resistant stainless steel vortex impeller
- SJE Rhombus® float switch with piggyback power plug




80 | 5 Year Warranty **100 | 5 Year Warranty**
Gallons Per Minute Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Switch Type | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|-------------|------|--------|----------|
| PAN92731 | 3/4 | 10 | SS/Cast Iron | 2" / 1-1/2" | Tether | 10' | 1/2" | 5 Years |
| PAN92751 | 3/4 | 10 | SS/Cast Iron | 2" / 1-1/2" | Vertical | 10' | 1/2" | 5 Years |
| PAN92181 | 1 | 12 | SS/Cast Iron | 2" / 1-1/2" | Tether | 10' | 1/2" | 5 Years |
| PAN92151 | 1 | 12 | SS/Cast Iron | 2" / 1-1/2" | Vertical | 10' | 1/2" | 5 Years |

Stainless Steel / Cast Iron

| Head | PAN92731/92751 | | PAN92181/92151 | |
|------|----------------|------|----------------|------|
| | GPM | GPH | GPM | GPH |
| 0' | 80 | 4800 | 100 | 6000 |
| 10' | 69 | 4140 | 82 | 4920 |
| 20' | 55 | 3300 | 63 | 3780 |
| 30' | 29 | 1740 | 44 | 2640 |
| 40' | - | - | 25 | 1500 |
| 50' | - | - | 7 | 420 |

Based on 2" PVC discharge pipe




HIGH-HEAD EFFLUENT PUMPS

SEWAGE PUMPS

The Panelli® sewage pump portfolio is tailored to address the demanding requirements of challenging applications, boasting performance capabilities of up to 140 GPM @ 0 ft. Whether seeking a standalone replacement pump or a comprehensive 18-inch or 24-inch pre-assembled pump and basin drop-in ready system, our offerings are poised to elevate operational efficacy.

Our sewage pumps are meticulously crafted from heavy-duty epoxy-coated cast iron and/or corrosion-resistant stainless steel, ensuring resilience in the face of rigorous applications. Engineered for enduring performance, these pumps are equipped with a solid copper-wound, thermally protected PSC motor, double O-ring seals, and heavy-duty mechanical shaft seals, guaranteeing sustained, noiseless, and leak-free functionality over extended periods. Notably, the inclusion of a stainless steel vortex impeller enables the pumps to effectively accommodate up to 2-inch solids.

- A** Carrying Handle
- B** Vertical or Tether Operation
- C** Permanent Split Capacitor Motor
- D** Solid Copper Motor Windings
- E** Double Seals on Motor Plate
- F** Stainless Steel Vortex Impeller
- G** Heavy Duty Shaft Seal



1/2 HP

Cast Iron



- Pump will lift water up to 25' of vertical height
- Rugged cast iron construction
- Easily handles 2" solids
- Large 2" discharge for high capacity pumping
- Stainless steel, non-clogging vortex impeller


80 Gallons Per Minute | **3 Year Warranty**

| Model | HP | Amps | Construction | Discharge Size | Switch Type | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|-------------|------|--------|----------|
| PAN93501 | 1/2 | 7.6 | Cast Iron | 2" | Tether | 10' | 2" | 3 Years |
| PAN93511 | 1/2 | 7.6 | Cast Iron | 2" | Vertical | 10' | 2" | 3 Years |

Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 80 | 4800 |
| 5' | 68 | 4080 |
| 10' | 60 | 3600 |
| 15' | 44 | 2640 |
| 20' | 13 | 780 |
| 25' | 2 | 120 |

Based on 2" PVC discharge pipe



1/2 HP

Stainless Steel / Cast Iron



- Pump will lift water up to 25' of vertical height
- Rugged cast iron and stainless steel construction
- Easily handles 2" solids
- Large 2" discharge for high capacity pumping
- Stainless steel, non-clogging vortex impeller


140 Gallons Per Minute | **3 Year Warranty**

| Model | HP | Amps | Construction | Discharge Size | Switch Type | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|-------------|------|--------|----------|
| PAN93781 | 1/2 | 12 | SS/Cast Iron | 2" | Tether | 15' | 1/2" | 3 Years |
| PAN93782 | 1/2 | 12 | SS/Cast Iron | 2" | Vertical | 15' | 1/2" | 3 Years |

Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 140 | 8400 |
| 5' | 123 | 7380 |
| 10' | 97 | 5820 |
| 15' | 72 | 4320 |
| 20' | 49 | 2940 |
| 25' | 25 | 1500 |

Based on 2" PVC discharge pipe



SUBMERSIBLE SEWAGE PUMPS

18"

Stainless Steel / Cast Iron

Pump Models:
93501/93511



Torque Stops



Pump Models:
93781/93782

- **Pump Features:**
 - Cast iron or stainless steel submersible sewage pumps
 - SJE Rhombus® vertical or tether float switch
 - Non-clogging stainless steel vortex impeller
 - Will easily handle 2" solids
- **Basin Features**
 - Corrosion resistant structural foam
 - Air tight molded reusable PVC gasket
 - 30 gallon capacity
 - 4" inlet hub, 2" discharge & vent
 - Built-in torque stops keep pump in place
- **Cover Options**
 - 18" Premium or premium split lid cover
- **Check Valve Features:**
 - Rubber flexible couplings & stainless steel clamps
 - Full flow design with 2" connections


80 | 3 Year Warranty
Gallons Per Minute

140 | 3 Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch Type | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|----------------|-------------|------|--------|----------|
| PAN93015 | 1/2 | 7.6 | Cast Iron | 2" | Side | Tether | 10' | 2" | 3 Years |
| PAN93020 | 1/2 | 7.6 | Cast Iron | 2" | Side | Vertical | 10' | 2" | 3 Years |
| PAN93078 | 1/2 | 12 | SS/Cast Iron | 2" | Side | Tether | 10' | 2" | 3 Years |
| PAN93080 | 1/2 | 12 | SS/Cast Iron | 2" | Side | Vertical | 10' | 2" | 3 Years |

| Performance | PAN93015 PAN93020 | | PAN93078 PAN93080 | |
|-------------|----------------------|-----|----------------------|-----|
| | Head | GPM | GPH | GPM |
| 0' | | 80 | 4800 | 140 |
| 5' | | 68 | 4080 | 123 |
| 10' | | 60 | 3600 | 97 |
| 15' | | 44 | 2640 | 72 |
| 20' | | 13 | 1380 | 49 |
| 25' | | 2 | 120 | 25 |

Based on 2" PVC discharge pipe



24"

Stainless Steel / Cast Iron



Torque Stops

Pump Models:
93501/93511

Pump Models:
93781/93782

- **Pump Features**
 - Cast iron or stainless steel submersible sewage pumps
 - SJE Rhombus® vertical or tether float switch
 - Non-clogging stainless steel vortex impeller
 - Will easily handle 2" solids
- **Basin Features**
 - Tough polyethylene construction
 - Gasket sealed liquid & airtight cover
 - 45 gallon capacity
 - 2" discharge & vent
 - Molded torque stops keep pump in place
 - Built-in anti float collar, prevents basin from floating
 - Integrated 360° lifting handle
- **Multiple hub options**

80 | 3 Year Warranty
Gallons Per Minute


140 | 3 Year Warranty
Gallons Per Minute

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Switch Type | Cord | Solids | Warranty |
|----------|-----|------|--------------|----------------|----------------|-------------|------|--------|----------|
| PAN93024 | 1/2 | 7.6 | Cast Iron | 2" | Side | Tether | 10' | 2" | 3 Years |
| PAN93026 | 1/2 | 7.6 | Cast Iron | 2" | Side | Vertical | 10' | 2" | 3 Years |
| PAN93082 | 1/2 | 12 | SS/Cast Iron | 2" | Side | Tether | 15' | 2" | 3 Years |
| PAN93084 | 1/2 | 12 | SS/Cast Iron | 2" | Side | Vertical | 15' | 2" | 3 Years |

- **Cover Options**
 - 24" premium or premium split lid cover
- **Check Valve Features**
 - Rubber flexible couplings & stainless steel clamps
 - Full flow design with 2" connections

| Performance | PAN93024 PAN93026 | | PAN93082 PAN93084 | |
|-------------|----------------------|-----|----------------------|-----|
| | Head | GPM | GPH | GPM |
| 0' | | 80 | 4800 | 140 |
| 5' | | 68 | 4080 | 123 |
| 10' | | 60 | 3600 | 97 |
| 15' | | 44 | 2640 | 72 |
| 20' | | 13 | 1380 | 49 |
| 25' | | 2 | 120 | 25 |

Based on 2" PVC discharge pipe



Our Panelli® range of Specialty pumps/kits offers a variety of solutions for efficiently transferring water from one location to another. These specialized pumps are designed to expedite installation of HVAC systems, descale tankless water heaters, safely transfer petroleum or water lawns from a nearby water source. All save you time up time for the next job. From charging polyglycol lines, emptying a water heater, or integrating a condensate pump into an HVAC system, we are here for you to provide the right tools for the job.

Tankless Water Heater Descaler Kit



Kit Includes:

- Pump
- 3.5 gallon pail
- Hoses
- Descaler solution

- All-in-one kit provides each necessary items to help clean and descale most tankless water heaters
- Dezcal® descaler helps clean most tankless water heaters from accumulated minerals that build up on the walls inside the tank's heat exchanger
- Oil-free motor design
- Non-clogging reinforced thermoplastic impeller
- 3/4" garden hose adapter included
- Descaler solution is non-toxic and biodegradable


32 Gallons Per Minute | **1 Year Warranty**

| Model | HP | Amps | Construction | Discharge Size | Discharge Type | Cord | Solids | Warranty |
|----------|-----|------|---------------|----------------|----------------|------|--------|----------|
| PAN91660 | 1/6 | 2.7 | Thermoplastic | 1" | Side | 8' | 1/8" | 1 Year |


Performance

| Head | GPM | GPH |
|------|-----|------|
| 0' | 32 | 1920 |
| 5' | 29 | 1740 |
| 10' | 24 | 1440 |
| 15' | 19 | 1140 |
| 20' | 12 | 720 |

Based on 1" PVC discharge pipe



Condensate Pumps



- Thermally protected, fan cooled motor
- ½ gallon collection tank
- Automatic operation
- 3/8" barbed discharge with built in check valve
- Four 1-1/8" inlet openings with removable caps
- Dual function NO (Normally Open) and NC (Normally Closed) safety switch, with 8" lead wires
- Stainless steel wall mount tabs included

88 | 3 Year Warranty
Gallons Per Hour

108 | 3 Year Warranty
Gallons Per Hour


100 | 3 Year Warranty
Gallons Per Hour

| Model | HP | Volts | Hz | Watts | Amps | Safety Switch | Cord | Max Temp | Warranty |
|----------|------|-------|-------|-------|------|---------------|------|----------|----------|
| PAN97150 | 1/50 | 115 | 60 | 65 | 1.2 | No | 6' | 140° F | 3 Years |
| PAN97152 | 1/50 | 115 | 60 | 65 | 1.2 | Yes | 6' | 140° F | 3 Years |
| PAN97200 | 1/30 | 115 | 60 | 80 | 1.5 | No | 6' | 140° F | 3 Years |
| PAN97202 | 1/30 | 115 | 60 | 80 | 1.5 | Yes | 6' | 140° F | 3 Years |
| PAN97233 | 1/30 | 230 | 50/60 | 65 | 0.6 | No | 6' | 140° F | 3 Years |
| PAN97230 | 1/30 | 230 | 50/60 | 65 | 0.6 | Yes | 6' | 140° F | 3 Years |

Stainless Steel

| | PAN97150 PAN97152 | PAN97200 PAN97202 | PAN97233 PAN97230 |
|------|----------------------|----------------------|----------------------|
| Head | GPH | GPH | GPH |
| 0' | 88 | 108 | 100 |
| 5' | 84 | 102 | 96 |
| 10' | 66 | 78 | 72 |
| 15' | 6 | 54 | 42 |
| 20' | - | 15 | 11 |

Based on 3/8" discharge



1 HP Portable Sprinkler

Stainless Steel



- Powerful 1 HP fan cooled, 115 volt TEFC motor
- Corrosion resistant stainless steel housing
- Integral carry handle for portability
- Convenient on/off switch
- 1" NPT Suction and discharge
- 165' total dynamic head
- Pressure up to 72 psi
- Garden hose adapters included




13.8 Gallons Per Minute | 1 Year Warranty

| Model | HP | Volts | Amps | Construction | Suction Size | Discharge Size | Max Pressure | Cord | Overload Protection | Warranty |
|----------|----|-------|------|-----------------|--------------|----------------|--------------|------|---------------------|----------|
| PAN96110 | 1 | 115 | 5.2 | Stainless Steel | 1" NPT | 1" NPT | 72 psi | 10' | Yes | 1 Year |

Performance

| Head | GPM | GPH |
|------|------|-----|
| 0' | 13.8 | 828 |
| 20' | 12.4 | 745 |
| 40' | 11 | 660 |
| 60' | 9.4 | 566 |
| 80' | 7.3 | 440 |
| 100' | 5.6 | 337 |
| 120' | 3.8 | 230 |
| 140' | 2.1 | 127 |

Based on 1" discharge



OIL-DEFENDER™ Elevator Sump Control System



- The Oil-Defender™ single phase simplex control panel is used for the safe operation of pumping, alarming, and monitoring of elevator sump pits, transformer vaults, and leachate well applications.
- The control panel will activate a pump to remove water from pits in accordance with ASME A17.1, stopping the pump before oil or other harmful substances enter the water supply.
- The control panel comes with a pre-installed female pump power receptacle, incoming system power cable, preset level sensor, alarm test/silence switch, and alarm buzzer.
- 6' cord option available



75 | 3 Year Warranty
Gallons Per Minute

80 | 3 Year Warranty
Gallons Per Minute


100 | 3 Year Warranty
Gallons Per Minute

| Kit Model | Pump Model | HP | Amps | Construction | Discharge Size | Cord | Solids | Warranty |
|-----------|------------|-----|------|--------------|----------------|------|--------|----------|
| PAN92055 | PAN92571 | 1/2 | 7.5 | SS/Cast Iron | 2" / 1-1/2" | 25' | 1/2" | 3 Years |
| PAN92075 | PAN92751 | 3/4 | 10 | SS/Cast Iron | 2" / 1-1/2" | 25' | 1/2" | 3 Years |
| PAN92100 | PAN92151 | 1 | 12 | SS/Cast Iron | 2" / 1-1/2" | 25' | 1/2" | 3 Years |

Performance

| | PAN92055 | | PAN92075 | | PAN92100 | |
|------|----------|------|----------|------|----------|------|
| Head | GPM | GPH | GPM | GPH | GPM | GPH |
| 0' | 75 | 4500 | 80 | 4800 | 100 | 6000 |
| 10' | 64 | 3840 | 69 | 4140 | 82 | 4920 |
| 20' | 49 | 2940 | 55 | 3300 | 63 | 3780 |
| 30' | - | - | 29 | 1740 | 44 | 2640 |
| 40' | - | - | - | - | 25 | 1500 |
| 50' | - | - | - | - | 7 | 420 |

Based on 2" PVC discharge pipe



Bronze Transfer Pumps

Bronze



- Loren Simer's original bronze paddle pump
- Made from 85/5/5/5 bronze
- Will develop 30 psi
- Stainless steel impeller shaft & fasteners
- Handles liquids up to 180° F
- Draining & filling heating and hot water systems
- Recommended motor size: 1/2 HP 1725 RPM
- Standard impeller handles most farm and industrial liquids*
- "X" type impeller handles most flammable & corrosive liquids*

* Not recommended for ethanol use


18 | 1 Year Warranty
Gallons Per Minute

28 | 1 Year Warranty
Gallons Per Minute

| Model | Suction/Discharge | Impeller Shaft Size | Construction | Impeller | Impeller Warranty | Pump Warranty |
|-------|-------------------|---------------------|-----------------|----------|-------------------|---------------|
| BP20 | 3/4" | 1/2" | 85/5/5/5 Bronze | Standard | 90 Days | 1 Year |
| BP20X | 3/4" | 1/2" | 85/5/5/5 Bronze | "X" Type | 90 Days | 1 Year |
| BP21 | 1" | 5/8" | 85/5/5/5 Bronze | Standard | 90 Days | 1 Year |
| BP21X | 1" | 5/8" | 85/5/5/5 Bronze | "X" Type | 90 Days | 1 Year |

| Head | BP20 BP20X | | BP21X BP21X | |
|------|---------------|------|----------------|------|
| | GPM | GPH | GPM | GPH |
| 5' | 18 | 1080 | 28 | 1680 |
| 10' | 16 | 960 | 25 | 1500 |
| 25' | 11 | 660 | 15 | 900 |
| 35' | 8 | 480 | 10 | 600 |
| 45' | 5 | 300 | 6 | 360 |
| 55' | 2 | 120 | 3 | 180 |
| 65' | 1 | 60 | .5 | 30 |

Performances based on using 1/2 HP, 1725 RPM motor



Bulldog Bronze Transfer Pump Systems

Bronze



- 1/2 HP - 120/240V farm duty motor**
- Complete kit for chemical, oil & non-explosive fluid transfer
- "X" type impeller handles most flammable & corrosive liquids*
- Includes two brass hose adapters
- Sturdy welded roll frame for ease of handling

18 | 1 Year Warranty
Gallons Per Minute




- 1/2 HP - 120/240V explosion-proof motor**
- Sturdy welded roll frame for ease of handling
- Includes on/off switch and 8' or 25' grounded power cord
- "X" type impeller handles most flammable & corrosive liquids*

28 | 1 Year Warranty
Gallons Per Minute

| Model | Bronze Pump Model | Pump Size | Cord | Explosion-Proof | Impeller | Impeller Warranty | Pump Warranty |
|----------|-------------------|-----------|------|-----------------|----------|-------------------|---------------|
| PAN90005 | BP20X | 3/4" | 8' | No | "X" Type | 90 Days | 1 Year |
| PAN90000 | BP21X | 1" | 8' | No | "X" Type | 90 Days | 1 Year |
| PAN90150 | BP20X | 3/4" | 25' | Yes | "X" Type | 90 Days | 1 Year |
| PAN90100 | BP21X | 1" | 25' | Yes | "X" Type | 90 Days | 1 Year |

| Head | PAN90005 PAN90000 | | PAN90150 PAN90100 | |
|------|----------------------|------|----------------------|------|
| | GPM | GPH | GPM | GPH |
| 5' | 18 | 1080 | 28 | 1680 |
| 10' | 16 | 960 | 25 | 1500 |
| 25' | 11 | 660 | 15 | 900 |
| 35' | 8 | 480 | 10 | 600 |
| 45' | 5 | 300 | 6 | 360 |
| 55' | 2 | 120 | 3 | 180 |
| 65' | 1 | 30 | .5 | 30 |



* Not recommended for ethanol use

** Motor manufacturer may vary

WELL PUMPS

At Panelli®, we provide an extensive range of well pumps and fully assembled systems tailored to meet the specific requirements of your clientele, thereby optimizing your efficiency. We build it, so you don't have to. Our complete line of well water offerings are meticulously designed with dual voltage (115/230 V) motors, glass-filled thermoplastic diffusers, and robust epoxy-coated cast iron to ensure consistent and reliable performance over time. We offer a diverse selection of well pump and system alternatives, encompassing both deep and shallow well pumps, to cater to your professional demands.



- Dual voltage motor (115/230v)
 - Rugged cast iron pump body for durability
 - Tough thermoplastic impeller
 - Glass filled thermoplastic diffuser
 - Cast iron seal plate
 - Pre-mounted, fully adjustable pressure switch
 - For shallow well applications up to 25' depth
- *Pre-assembled to 24L or 50L pressure tank*

| Model | HP | Volts | Amps | Suction Size | Discharge Size | Pressure Switch | Max Pressure | Max Flow Rate | Overload Protection | Pressure Tank Size | Warranty |
|----------|-----|---------|---------|--------------|----------------|-----------------|--------------|---------------|---------------------|--------------------|----------|
| PAN94505 | 1/2 | 115/230 | 6.4/3.2 | 1-1/4"NPT | 1" | 20/40 psi | 67 psi | 600 GPH | Yes | - | 3 Years |
| PAN94525 | | | | | | | | | | 24L | |
| PAN94553 | | | | | | | | | | 50L | |

PERFORMANCES

| Total Suction Lift (feet) | Discharge Pressure - PSI | | | | Max Pressure |
|---------------------------|--------------------------|-----|-----|-----|--------------|
| | 20 | 30 | 40 | 50 | |
| | Gallons per hour | | | | |
| 5' | 744 | 678 | 570 | 360 | 67 psi |
| 10' | 678 | 642 | 528 | 312 | |
| 15' | 618 | 600 | 492 | 270 | |
| 20' | 582 | 570 | 450 | 228 | |
| 25' | 534 | 528 | 408 | 198 | |

| Model | HP | Volts | Amps | Suction Size | Discharge Size | Pressure Switch | Max Pressure | Max Flow Rate | Overload Protection | Pressure Tank Size | Warranty |
|----------|-----|---------|---------|--------------|----------------|-----------------|--------------|---------------|---------------------|--------------------|----------|
| PAN94705 | 3/4 | 115/230 | 7.8/3.9 | 1-1/4"NPT | 1" | 20/40 psi | 74 psi | 708 GPH | Yes | - | 3 Years |
| PAN94725 | | | | | | | | | | 24L | |
| PAN94753 | | | | | | | | | | 50L | |

PERFORMANCES

| Total Suction Lift (feet) | Discharge Pressure - PSI | | | | Max Pressure |
|---------------------------|--------------------------|-----|-----|-----|--------------|
| | 20 | 30 | 40 | 50 | |
| | Gallons per hour | | | | |
| 5' | 816 | 750 | 678 | 528 | 74 psi |
| 10' | 732 | 726 | 648 | 480 | |
| 15' | 654 | 624 | 612 | 438 | |
| 20' | 594 | 564 | 540 | 414 | |
| 25' | 540 | 516 | 468 | 396 | |

| Model | HP | Volts | Amps | Suction Size | Discharge Size | Pressure Switch | Max Pressure | Max Flow Rate | Overload Protection | Pressure Tank Size | Warranty |
|----------|----|---------|------|--------------|----------------|-----------------|--------------|---------------|---------------------|--------------------|----------|
| PAN94105 | 1 | 115/230 | 10/5 | 1-1/4"NPT | 1" | 20/40 psi | 79 psi | 780 GPH | Yes | - | 3 Years |
| PAN94125 | | | | | | | | | | 24L | |
| PAN94153 | | | | | | | | | | 50L | |

PERFORMANCES

| Total Suction Lift (feet) | Discharge Pressure - PSI | | | | Max Pressure |
|---------------------------|--------------------------|-----|-----|-----|--------------|
| | 20 | 30 | 40 | 50 | |
| | Gallons per hour | | | | |
| 5' | 918 | 846 | 750 | 486 | 79 psi |
| 10' | 804 | 780 | 720 | 408 | |
| 15' | 738 | 726 | 660 | 342 | |
| 20' | 666 | 654 | 630 | 270 | |
| 25' | 582 | 570 | 558 | 216 | |

SHALLOW WELL JET PUMP AND TANK SYSTEMS



- Dual voltage motor (115/230v)
 - Rugged cast iron pump body for durability
 - Tough thermoplastic impeller
 - Glass filled thermoplastic diffuser
 - Cast iron seal plate
 - Pre-mounted, fully adjustable pressure switch
 - Convertible to be used in shallow well applications up to 25' depth or in deep well applications up to 80' depth
- *Pre-assembled to 24L or 50L pressure tank*

| Model | HP | Volts | Amps | Suction Size | Discharge Size | Pressure Switch | Max Pressure | Max Flow Rate | Overload Protection | Pressure Tank Size | Warranty |
|----------|-----|---------|---------|--------------|----------------|-----------------|--------------|---------------|---------------------|--------------------|----------|
| PAN94515 | 1/2 | 115/230 | 6.4/3.2 | 1-1/4"NPT | 1" | 20/40 psi | 58 psi | 420 GPH | Yes | - | 3 Years |
| PAN94520 | | | | | | | | | | 24L | |
| PAN94513 | | | | | | | | | | 50L | |

SINGLE PIPE SHALLOW WELL PERFORMANCES

| Total Suction Lift (feet) | Discharge Pressure - PSI | | | | Max Pressure |
|---------------------------|--------------------------|-----|-----|-----|--------------|
| | 20 | 30 | 40 | 50 | |
| | Gallons per hour | | | | |
| 5' | 774 | 708 | 600 | 450 | 58 psi |
| 10' | 576 | 546 | 516 | 396 | |
| 15' | 528 | 492 | 462 | 360 | |
| 20' | 462 | 438 | 414 | 354 | |
| 25' | 432 | 372 | 348 | 276 | |

TWIN PIPE DEEP WELL PERFORMANCES

| PUMPING DEPTH IN FEET | | | | | |
|-----------------------|-----|-----|-----|-----|-----|
| 30' | 40' | 50' | 60' | 70' | 80' |
| 228 | 180 | 120 | 72 | 36 | - |

| Model | HP | Volts | Amps | Suction Size | Discharge Size | Pressure Switch | Max Pressure | Max Flow Rate | Overload Protection | Pressure Tank Size | Warranty |
|----------|-----|---------|---------|--------------|----------------|-----------------|--------------|---------------|---------------------|--------------------|----------|
| PAN94715 | 3/4 | 115/230 | 7.8/3.9 | 1-1/4"NPT | 1" | 20/40 psi | 61 psi | 588 GPH | Yes | - | 3 Years |
| PAN94720 | | | | | | | | | | 24L | |
| PAN94713 | | | | | | | | | | 50L | |

SINGLE PIPE SHALLOW WELL PERFORMANCES

| Total Suction Lift (feet) | Discharge Pressure - PSI | | | | Max Pressure |
|---------------------------|--------------------------|-----|-----|-----|--------------|
| | 20 | 30 | 40 | 50 | |
| | Gallons per hour | | | | |
| 5' | 774 | 708 | 600 | 450 | 61 psi |
| 10' | 576 | 546 | 516 | 396 | |
| 15' | 528 | 492 | 462 | 360 | |
| 20' | 462 | 438 | 414 | 354 | |
| 25' | 432 | 372 | 348 | 276 | |

TWIN PIPE DEEP WELL PERFORMANCES

| PUMPING DEPTH IN FEET | | | | | |
|-----------------------|-----|-----|-----|-----|-----|
| 30' | 40' | 50' | 60' | 70' | 80' |
| 252 | 246 | 204 | 144 | 96 | 54 |

| Model | HP | Volts | Amps | Suction Size | Discharge Size | Pressure Switch | Max Pressure | Max Flow Rate | Overload Protection | Pressure Tank Size | Warranty |
|----------|----|---------|------|--------------|----------------|-----------------|--------------|---------------|---------------------|--------------------|----------|
| PAN94115 | 1 | 115/230 | 10/5 | 1-1/4"NPT | 1" | 20/40 psi | 71 psi | 630 GPH | Yes | - | 3 Years |
| PAN94120 | | | | | | | | | | 24L | |
| PAN94113 | | | | | | | | | | 50L | |

SINGLE PIPE SHALLOW WELL PERFORMANCES

| Total Suction Lift (feet) | Discharge Pressure - PSI | | | | Max Pressure |
|---------------------------|--------------------------|-----|-----|-----|--------------|
| | 20 | 30 | 40 | 50 | |
| | Gallons per hour | | | | |
| 5' | 912 | 894 | 864 | 552 | 71 psi |
| 10' | 738 | 792 | 738 | 486 | |
| 15' | 624 | 708 | 630 | 444 | |
| 20' | 552 | 564 | 546 | 390 | |
| 25' | 510 | 480 | 480 | 324 | |

TWIN PIPE DEEP WELL PERFORMANCES

| PUMPING DEPTH IN FEET | | | | | |
|-----------------------|-----|-----|-----|-----|-----|
| 30' | 40' | 50' | 60' | 70' | 80' |
| 312 | 270 | 240 | 210 | 192 | 138 |

Tether Float Switches



- SJE Rhombus®
- Non-mercury tether float switch
- Sump / Sewage wide angle float switch with piggyback plug



92040

92096

| Model | Amps | Max Liquid Temp | Volts | Cord |
|-------|------|-----------------|-------|------|
| 92000 | 10 | 140° | 120 | 10' |
| 92005 | 10 | 140° | 120 | 25' |
| 92059 | 13 | 140° | 120 | 15' |
| 92006 | 13 | 140° | 120 | 25' |
| 92040 | 15 | 140° | 120 | 10' |
| 92096 | 15 | 140° | 120 | 15' |

Vertical Float Switches



- SJE Rhombus®
- Non-mercury vertical float switch with piggyback plug



99195
Vertical Float
Switch Bracket

- Universal with most vertical switches

| Model | Amps | Max Liquid Temp | Volts | Cord |
|-------|------|-----------------|-------|------|
| 92010 | 10 | 140° | 120 | 10' |
| 92025 | 10 | 140° | 120 | 25' |
| 92015 | 13 | 140° | 120 | 15' |
| 92014 | 13 | 140° | 120 | 25' |

Alarm Systems



92060



- Monitors liquid levels in sump & sewage basins, holding tanks and other water applications
- Non-corrosive NEMA enclosure, rated for indoor use
- 9 Volt battery backup (not included)
- 87 Decibel alarm horn with low battery chirp
- Comes complete with alarm, 15' float switch and mounting clip



92120



- Monitors liquid levels in sump & sewage basins, holding tanks and other water applications
- Enclosure meets type 3R water-tight standard and is rated for outdoor use
- Automatic alarm reset, horn silence switch, and alarm test switch
- 85 Decibel alarm horn with illuminated alarm beacon for visual notification
- Comes complete with alarm, 25' float switch and mounting clip




92122



- Removable cover for easier field wiring while the internal circuitry remains protected
- External mounting tabs for easy installation
- Enclosure meets Type 3R water-tight standard
- 82 Decibel alarm horn with illuminated alarm beacon for visual notification
- Automatic alarm reset
- Alarm test/horn silence switch
- Comes complete with alarm, 15' float switch and mounting clip

Sump & Sewage Basins & Covers



| Model | Size | Description | Capacity | Inlet | Torque Stops Standard |
|----------|-----------|-----------------------------------|----------|-------|-----------------------|
| PAN99275 | 18"x30" | Structural foam sewage basin | 30 Gal | 4" | Yes |
| PAN99344 | 24"x24" | Poly sewage basin | 45 Gal | 4" | Yes |
| PAN99320 | 18"x24" | Structural foam sump basin | 22 Gal | 4" | Yes |
| PAN99313 | 18"x17.5" | Structural foam crawl space basin | 15 Gal | n/a | n/a |
| PAN99294 | 18"x6" | 6" basin extension | n/a | n/a | n/a |
| PAN99295 | 18"x12" | 12" basin extension | n/a | n/a | n/a |

| Model | Size | Description | Discharge | Vent Size |
|-------|------|--|------------------|-----------|
| 99276 | 18" | Structural Foam Sewage Basin Cover for 99300 | 2" | 2" |
| 99260 | 18" | Split Lid Structural Foam Sewage Basin Cover for 99300 | 2" | 2" |
| 99343 | 18" | Structural Foam Standard Sump Basin Cover for 99320 | Fits 1-1/2" Pipe | |
| 99308 | 18" | Structural Foam Crawl Space Basin Cover, Slotted, 1-1/2" for 99313 | n/a | n/a |
| 99342 | 18" | Structural Foam Sump Basin Cover for 99320 | 1-1/2" | n/a |


Remote Drain Basin



99262

- Structural foam construction
- Molded reusable PVC seal
- 6 gallon capacity
- 15" x 13.5"
- 1-1/2" inlet, 1-1/2" outlet and vent
- Corrosion resistant

The Block



99501

- Use instead of bricks to raise pump off bottom of basin
- Fits most Panelli plastic and cast iron sump pumps
- Easily mounts to pump base
- Made from durable ABS
- Helps prevent clogging and switch malfunction

Swing Check Valves



99505



99555



99507
99509



99547
99549



99508



99477
99479



99544



99522



99502



99529

| Model | Material | Size & Connection | Type |
|--|----------|---|-------|
| UNIVERSAL CHECK VALVES | | | |
| 99505 | ABS | 1-1/4" FPT or 1-1/2" MPT x 1-1/4" FPT or 1-1/2" MPT | SWING |
| 99555 | ABS | 1-1/4" FPT/MPT or 1-1/2" FPT/MPT x 1-1/4" FPT/MPT or 1-1/2" FPT/MPT | SWING |
| MPT x BARB/SPG CHECK VALVES | | | |
| 99507 | ABS | 1-1/4" MPT x 1-1/4" barb or 1-1/2" SPG | SWING |
| 99509 | ABS | 1-1/2" MPT x 1-1/4" barb or 1-1/2" SPG | SWING |
| 99547 | PVC | 1-1/4" MPT x 1-1/4" barb or 1-1/2" SPG | SWING |
| 99549 | PVC | 1-1/2" MPT x 1-1/4" barb or 1-1/2" SPG | SWING |
| 99508 | ABS | 1-1/2" MPT x 1-1/2" barb | SWING |
| RUBBER COUPLING CHECK VALVES | | | |
| 99544 | ABS | 1-1/4" x 1-1/4" | SWING |
| 99522 | ABS | 1-1/2" x 1-1/2" | SWING |
| 99529 | ABS | 2" x 2" | SWING |
| 99502 | ABS | 1-1/4" or 1-1/2" x 1-1/4" or 1-1/2" | SWING |
| MPT x RUBBER COUPLING (RC) CHECK VALVES | | | |
| 99477 | ABS | 1-1/4" MPT x 1-1/4" or 1-1/2" RC | SWING |
| 99479 | ABS | 1-1/2" MPT x 1-1/4" or 1-1/2" RC | SWING |

- Durable ABS or PVC construction
- Weighted flapper seal
- Full flow design reduces flow loss
- Pressure rating:
 - 4.3 PSI @ 140° F (60° C) Rubber Coupling Installation
 - 25 PSI @ 140° F (60° C) Solvent Weld Installation
- 300 Grade Stainless Steel Clamps (Rubber Coupling Models)
- Maximum fluid temperature 140° F (60° C)
- Not for use with compressed air, gasses or potable water

PVC Check Valves



99526
99527



99524
99525



99582
99579



99590
99588



99545

- Constructed from Type 1 PVC
- Weighted flapper seal
- Full flow design reduces flow loss
- Can be installed vertically or horizontally
- Pressure rating: 125 PSI @ 75° F (24° C)
- Maximum fluid temperature 140° F (60° C)
- Conforms to ASTM D2466
- Not for use with compressed air, gasses or potable water

| Model | Material | Size & Connection | Type |
|---|----------|-------------------------------------|----------------|
| SOLVENT WELD CHECK VALVES - SLIP x SLIP | | | |
| 99526 | PVC | 1-1/2" X 1-1/2" | SWING |
| 99527 | PVC | 2" X 2" | SWING |
| COMPRESSION CHECK VALVES - COMPRESSION x COMPRESSION | | | |
| 99524 | PVC | 1-1/2" X 1-1/2" | SWING |
| 99525 | PVC | 2" X 2" | SWING |
| BALL / CHECK VALVE COMBINATION - UNION x SLIP | | | |
| 99582 | PVC | 1-1/2" UNION X 1-1/2" SLIP | SWING |
| 99579 | PVC | 2" UNION X 2" SLIP | SWING |
| QUIET TRUE UNION CHECK VALVES - UNION x UNION | | | |
| 99590 | PVC | 1-1/2" X 1-1/2" | 1/2 lb. SPRING |
| 99588 | PVC | 2" X 2" | 1/2 lb. SPRING |
| SUMP PUMP CHECK VALVE - COMPRESSION | | | |
| 99545 | PVC | 1-1/4" or 1-1/2" x 1-1/4" or 1-1/2" | SWING |

Brass Check Valves



- Lead free brass valve body & poppet
- Stainless steel spring and fasteners
- NBR O-ring
- 200 PSI maximum pressure
- 180°F maximum temperature

| Model | Size | Material | Max Temp | Max PSI |
|-------|--------|----------|----------|---------|
| 99488 | 1-1/4" | Brass | 180° | 200 |
| 99487 | 1" | Brass | 180° | 200 |

Brass Foot Valves



- Lead free brass valve body & poppet
- Stainless steel strainer, spring and fasteners
- NBR O-ring
- 200 PSI maximum pressure
- 180°F maximum temperature

| Model | Size | Material | Max Temp | Max PSI |
|-------|--------|----------|----------|---------|
| 99495 | 1-1/4" | Brass | 180° | 200 |
| 99496 | 1" | Brass | 180° | 200 |

PVC Foot Valves




- Durable, non-corrosive PVC construction
- Maintains prime in pump system
- Maximum working pressure 150 PSI @ 73° F
- Helps prevent debris from entering pump

| Model | Size | Material | Max Temp |
|-------|-------------|----------|----------|
| 99489 | 1-1/4" FNPT | PVC | 150° |
| 99492 | 1" FNPT | PVC | 150° |
| 99491 | 3/4" FNPT | PVC | 150° |

25' Lay-Flat Discharge Hose Kit

PAN99621

- For use with most sump and utility pumps with 1-1/4" or 1-1/2" discharge
- Easily rolls up for compact storage
- Adapter fittings included
- 19 PSI max working pressure



Kit includes:

- A. 1-1/2" x 25' reinforced PVC lay-flat hose
- B. Stainless steel hose clamp
- C. 1-1/4" FPT x 1-1/4" FPT or 1-1/2" MPT coupling / adapter
- D. 1/4" MPT x 1-1/2" barb adapter

50' Reinforced Lay-Flat Discharge Hose Kit

PAN99620

- 50' reinforced industrial 1-1/2" discharge hose
- Cam-lock fittings included
- Expandable: Includes fitting (B) to connect multiple hoses together
- For use with most pumps with 1-1/4" or 1-1/2" discharge
- Preassembled and ready to use
- 116 PSI max working pressure



Kit includes:

- A. 1-1/2" x 50' reinforced industrial lay-flat hose with 1-1/2" female Cam-lock and 1-1/2" hose barb
- B. 1-1/2" male Cam-lock x 1-1/2" hose barb
- C. 1-1/2" male Cam-lock x 1-1/4" MPT
- D. 1-1/4" FPT x 1-1/4" FPT or 1-1/2" MPT coupling
- E. Stainless steel hose clamp

Pump Hose Kits



PAN99624



PAN99625

- For use with most pumps with a discharge size of 1-1/4" or 1-1/2"
- For permanent or temporary use
- High quality poly drainage tubing
- Includes adapter(s) with rust resistant hose clamp
- Easy installation

| Model | Hose Size | Description | Adapters Included | Hose Clamp |
|----------|--------------|--------------------|-------------------|------------|
| PAN99624 | 1-1/4" x 24" | Universal Hose Kit | 1-1/4" and 1-1/2" | Yes |
| PAN99625 | 1-1/2" x 24" | 1-1/2" Hose Kit | 1-1/2" | Yes |

Adapters



| 99001 | 99003 | 99004 | 99005 | 99006 | 99007 |
|--------------------------------------|----------------------------------|-------------------------|--------------------------------------|--------------------------------------|---------------------------------------|
| 1-1/2" MPT x 3/4" garden hose thread | 1" FPT x 3/4" garden hose thread | 1-1/4" MPT x 1-1/2" FPT | 1-1/4" MPT x 3/4" garden hose thread | 1-1/4" FPT x 3/4" garden hose thread | 1-1/4" FPT x 1-1/2" MPT or 1-1/4" FPT |

Pressure Gauges



99200



99203



- Steel case with glass lens
- 2" Easy-read dial
- Lead free brass connection safe for potable water
- General purpose gauge for water pumps and pump systems
- Not for use with oxygen, natural gas or propane
- 0-100 PSI

| Model | Connection |
|-------|----------------------------|
| 99200 | 1/8" MPT Center Back Mount |
| 99203 | 1/4" MPT Lower Mount |

Pressure Switches



99243/99244



99245

- Universal replacement pump switch for pumps with 1/4" NPT connection
- Diaphragm activated
- Easy to install
- Two ground screws
- Corrosion resistant

| Model | PSI | Low Pressure Cutoff |
|-------|-------|---------------------|
| 99243 | 30/50 | No |
| 99244 | 20/40 | No |
| 99245 | 20/40 | Yes |

Brass Tank Tee



99485

- Used to connect water tanks to pipe and pumps and allow water to flow throughout the well water system.
- Lead Free Brass
- Center to End Length: 10"
- Tank Connection: 1" MPT
- In-Line Connections: 1" MPT or 3/4" FPT
- Accessory Ports: (2) 1/4" FPT & (2) 1/2" FPT

CONTACT US

CUSTOMER SERVICE

Mon - Fri: 8am - 8pm CT | Sat - Sun: 10am - 5pm CT

customer.service@pedrollogroupusa.com or **800.495.9278**



SALES

DAVID CALDWELL

Director of Business Development, Wholesale
david@pedrollogroupusa.com

ANDY LUNDGREN

Director of Sales, Wholesale
andy.lundgren@pedrollogroupusa.com

The background of the entire page is a photograph of two black submersible pumps. They are positioned on a highly reflective surface, creating clear reflections. The pump on the right is more prominent, featuring a carrying handle and a power cord. The pump on the left is partially obscured. The background is a light, neutral color, and there are some diagonal blue and grey graphic elements on the right side.

PANELLI®
Italian excellence since 1906



Panelli Pumps | 45 Maryland Avenue E | St. Paul, MN 55117 USA | 800-495-9278