



Italian excellence since 1906

PAN92511 1/2 HP Sump Pump

- Energy efficient 1/2 HP split capacitor motor. Lower amp draw, runs cooler, lasts longer.
- Solid cast iron pump base & housing. No plastic parts to crack or break.
- Corrosion resistant powder coated epoxy finish.
- Hermetically sealed oil-cooled motor for long pump life.
- Reinforced thermoplastic impeller for high volume pumping.
- 1-1/2" NPT discharge
- Handles up to 1/2" solids.
- Automatic operation with vertical float switch.
- Float switch features a piggyback plug which allows for manual or automatic operation.
- Motor is thermally protected with automatic reset thermal protector.
- Stainless steel motor shaft
- Carbon/ceramic/stainless steel mechanical shaft seal.
- Upper and lower ball bearings.
- Stainless steel fasteners
- Every unit is 100% pressure tested.



4200 GPH
5 Year Warranty




PAN92511 1/2 HP Sump Pump

Motor Specifications	
Horsepower	1/2 HP
Voltage	120
Amps	7.6
Hertz	60 Hz
Phase	Single
RPM	3450 RPM
Motor Type	Permanent Split Capacitor (PSC)
Insulation	Class A
Circuit Requirements	15 amp (min) individual circuit
Duty Rating	Continuous*
Shaft Seal	Carbon/ceramic and stainless steel
Motor Shaft	Stainless Steel
Upper Motor Bearing	Ball Bearing
Lower Motor Bearing	Ball Bearing
Cooling	Oil cooled
Motor Protection	Auto reset thermal overload protector

*For continuous operation, the water depth must be at least 6" to prevent the motor from overheating.

Pump Specifications	
Discharge Size	1-1/2" NPT
Cord Length	10'
Cord Type	SJTW, UL listed, 3-wire, 18 gauge
Pump Housing	Cast iron
Pump Base	Cast iron
Impeller Material	Stainless steel
Impeller Type	Reinforced thermoplastic
Gasket	Buna-N
Solids Handling	1/2" spherical
Liquid Temp. Range	32°- 120° F
Operation	Automatic or non-automatic
Fasteners	Stainless steel
Max Flow Rate	70 Gallons per minute
Maximum Head	25 feet
Max Pressure	10.8 psi
Weight	24.0 lbs

Automatic Switch Specifications	
Type	SJE Rhombus Vertical Master II
Switch on point	8.5"
Switch off point	3"
Material	High impact PVC
Cord Length	10'
Cord Type	SJOW, UL listed, 2-wire, 18 gauge



PERFORMANCE CHART

Head	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.	25 ft.
GPM	70	66	58	48	25	10
GPH	4200	3960	3480	2880	1500	600

Dimensions

